

NATIONAL TYPE EVALUATION PROGRAM

Certificate of Conformance for Weighing and Measuring Devices

For:

Computing Scale Digital Electronic

Models: A51Pxyz and A71Pxyz n_{max} : 3 000 / Multi-Interval

e_{min}: (see below)

Capacity: 15 to 60 lb (6 to 30 kg)

Platform: 13.2 in x 9.4 in (337mm x 240 mm)

Accuracy Class: III

Submitted By:

Ohaus Corporation 7 Campus Drive

Suite 310

Parsippany, NJ 07054 Tel: 973-377-9000 ext. 7032

Fax: 973-944-7177 Contact: Robert Hansen

Email: bob.hansen@ohaus.com
Web site: www.ohaus.com

Standard Features and Options

- Automatic Zero Tracking (AZT)
- Initial Zero Setting Mechanism (IZSM)
- Semi-Automatic (Push Button) Zero
- Keyboard Tare
- Programmable Tare (A71 models Only)
- Semi-Automatic (push-button) Tare
- Tare Save Key
- AC Power

- DC/ Battery Power
- Alphanumeric Display
- Liquid Crystal Display
- Customer Dual Display
- Gross/Tare/Net Display
- RS-232
- External Unit Conversion Key lb/kg
- Power Save Feature (Auto Shut Off)

Load Cell Used:

• Mettler-Toledo AMI 11, 22, 40 kg (Non-NTEP)

Models	Capacity x d (lb)	Capacity x d (kg)	n _{max}
A51P6Lz & A51P6TLz	15 x 0.005	6 x 0.002	3000
A51P15Lz & A51P15TLz	30 x 0.010	15 x 0.005	3000
A51P30Lz & A51P30TLz	60 x 0.02	30 x 0.01	3000
*A71P15DNz & A71P15DTNz	15 x 0.005 / 30 x 0.01	6 x 0.002 / 15 x 0.005	3000 (each range)
*A71P30DNz & A71P30DTNz	30 x 0.01 / 60 x 0.02	15 x 0.005 / 30 x 0.01	3000 (each range)
*Multi-interval models			

Temperature Range: -10 °C to 40 °C (14 °F to 104 °F)

This device was evaluated under the National Type Evaluation Program and was found to comply with the applicable technical requirements of "NIST Handbook 44: Specifications, Tolerances and Other Technical Requirements for Weighing and Measuring Devices." Evaluation results and device characteristics necessary for inspection and use in commerce are on the following pages.

Kurt Floren

Chairman, NCWM, Inc.

Chairman, National Type Evaluation Program Committee

Issued: February 2, 2012

1135 M Street, Suite 110 / Lincoln, Nebraska 68508

The National Conference on Weights and Measures (NCWM) does not approve, recommend or endorse any proprietary product or material, either as a single item or as a class or group. Results shall not be used in advertising or sales promotion to indicate explicit or implicit endorsement of the product or material by the NCWM.





Ohaus Corporation

Computing Scale / A51Pxyz and A71Pxyz

Application: General purpose computing scale for retail use.

<u>Identification</u>: A self-destructive identification label is attached to the right side of the housing.

Sealing: The device is sealed using a wire seal threaded through the heads of two (2) screws located on the bottom housing.

<u>Test Conditions</u>: The emphasis of the evaluation was on device design, operation, marking, performance, and compliance with influence factor requirements. Models submitted for evaluation were A71P15DNz and A71P30DTNz. Tests to verify compliance with zero, zone of uncertainty and motion detection requirements were performed. A checklist was completed and several increasing/decreasing and shift tests were performed. The scale was tested over a temperature range of 10 °C to 40 °C (32 °F to 104 °F). A load of approximately one-half capacity was applied to the scale over 100 000 times. The scale was tested periodically over this time. Voltage variation tests were also performed.

This device was evaluated by Measurement Canada under the Mutual Recognition Agreement (MRA) and the technical data was reviewed by the Maryland NTEP laboratory.

Evaluated By: R. Henshaw (MC); E. A. Payne, Jr. (MD)

<u>Type Evaluation Criteria Used:</u> NIST, <u>Handbook 44: Specifications, Tolerances and Other Technical Requirements for Weighing and Measuring Devices, 2012. NCWM, Publication 14: Weighing Devices, 2011.</u>

<u>Conclusion</u>: The results of the evaluation and information provided by the manufacturer indicate the device complies with applicable requirements.

Information Reviewed By: J. Truex (NCWM)

Examples of Device:





Model A51PxLz



Model A51PxTLz





Model A71PxDNz



Model A71PxDTNz